




Simply effective in every way



Valves are suitable for long-lasting operation because of special sealing construction. Low operating torque of the valve prevents of the valve blocking.

ZVQ 2000, 2-way zone valves, are suitable for open/close and ZVQ 3000, 3-way zone valves, are suitable for diverting or changeover applications.

Zone valves ZVQ are motorized with actuators series AQ5 making a compact unit with high regulating accuracy and easy installation with a quick system that allows for assembly and disassembly the actuator in a simple, rapid, and secure way.



# Valves you can trust - Shutting down problems, opening up solutions

## Features and options:

### Valves:

- · Internal or external thread
- 2-way valves
- 3-way horizontal / vertical valves
- DN15 ÷ DN25
- · Low operating torque
- · Quick connection to the actuator
- Tight-sealing valves prevents circulation losses
- · Blow-out proof stem
- · For open/close and diverting applications





### Actuators:

- 2-point control / 3-point control
- · Quick mounting of the actuator
- · Mistake-proofing assembly of the actuator
- · Compact and robust structure
- Running time 20s/90°; 40s/90°
- Available with cable or Molex connector
- Available with or without manual control
- Flexible design with many customization options









Product range of zone valves

**ZVQ 2000** 2-way zone valves



**ZVQ 3000HL** 3-way zone valves L ball



**ZVQ 3000HT** 3-way zone valves T ball



**ZVQ 3000V** 3-way zone valves L-L ball







**»Simplicity** »Reliability and robustness »Quick mounting »High energy efficiency »High modularity

ZVQ2000 and ZVQ3000 valves are motorized with AQ5 series actuators forming compact zone units.











# **Actuators: Moving ideas into action**


# AQ5 actuators\*



7 GO doldatoro						
Туре	Control signal	Torque (Nm)	Running time	Voltage	Connection	Manual control
AQ5F00M-2P	2 Point	5 Nm	20s/90°	230VAC	Molex	No
AQ5F00C-2P	2 Point	5 Nm	20s/90°	230VAC	Cable	No
AQ5F01M-2P	2 Point	5 Nm	20s/90°	230VAC	Molex	Yes
AQ5F01C-2P	2 Point	5 Nm	20s/90°	230VAC	Cable	Yes

<sup>\*</sup>Valves can also be used in combination with other actuators from the AQ5 product range.

# Valve type code:



ZV=zone valve

2-way zone valves



Туре	DN	Connection	Kvs	
ZVQ2115	15	Rp 1/2"	20	
ZVQ2120	20	Rp 3/4"	45	M
ZVQ2125	25	Rp 1"	60	
ZVQ2215	15	G 3/4"	20	M
ZVQ2220	20	G 1"	45	$+\infty$
ZVQ2225	25	G 1 1/4"	60	

#### 3-way zone valves L-L ball



. (	Kvs	Connection	DN	Гуре
<b>←</b>	9	Rp 3/4"	20	ZVQ3120V
6	14	Rp 1"	25	ZVQ3125V
Š	9	G 1"	20	ZVQ3220V
- 7	14	G 1 1/4"	25	ZVQ3225V

#### AQ5 F00M-2P L

Valve position indication: L=3-wayHL,3-wayV ;T=3-wayHT;not spec-=2-way Control signal 2P=2-point, 3P=3-point, MC=Modulating Connection: M=Molex, C=Cable Manual control: 0=without manual control, 1=with manual control -Voltage: 0=230VAC, 1=24VAC, 2=24VAC/DC Running time: F=20s/90°, G=40s/90°, H=55s/90°, I=110s/90° AQ5=Actuator with quick connection, max.torque 5 Nm

# 3-way zone valves L ball




Туре	DN	Connection	Kvs
ZVQ3120HL	20	Rp 3/4"	9
ZVQ3125HL	25	Rp 1"	14
ZVQ3220HL	20	G 1"	9
ZVQ3225HL	25	G 1 1/4"	14



## 3-way zone valves T ball



	ZVQ3125HT	25	
	ZVQ3132HT	32	
	ZVQ3225HT	25	
	ZVQ3232HT	32	



12.5

8

12,5

# Product range of zone units

ZA5 2000-2P 2-way zone unit



ZA5 3000HL-2P 3-way zone unit L ball



ZA53000HT -2P 3-way zone unit T ball



ZA5 3000V-2P 3-way zone unit L-L ball

25

16

25



Rp 1" Rp 1 1/4"

G 1 1/4"

G 1 1/2"



HVACO d.o.o. 18000 Niš

www.hvaco.rs

email: info@hvaco.rs www.hvaco.rs